








- NOTE:
1. Rating: DC30V 0.1A
 2. OP: 9.50±0.8
 3. Operating force: 30±15gf
 4. Mechanical Life: 3,000,000

⑦	Lever	1	Stainless Steel			
⑥	Shrapnel	1	Beryllium Copper			
⑤	Contact	1	Ag			
④	Terminal	3	Bross(0.52t)	Plating silver		
③	Housing	1	PBT	White		
②	Knob	1	PBT	White		
①	Cover	1	PBT	Black		
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	ELECTRONICS CO.,LTD	
DRAWN	J.X.Zhang	2013/11/6		
CHECKED				
APPROVALS				

TITILE:	MICRO SWITCHS
PART NO.	K9-1267G-G166

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	30~0.1t	±0.30	ANGLE	UNIT:	SCALE:	PROD.	SHEET
	A		NEW				10~0.30	±0.20		±2'	mm	1:1		1 OF 1
							5~0.10	±0.15						



- NOTE:
1. Rating: DC30V 0.1A
 2. OP: 9.00±0.8
 3. Operating force: 30±15gf
 4. Mechanical Life: 3,000,000

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
①	Cover	---	1	PBT	Black	
②	Knob	---	1	POM	White	
③	Housing	---	1	PBT	White	
④	Terminal	---	3	Bross(0.52t)	Plating silver	
⑤	Contact	---	1	Ag	---	
⑥	Shrapnel	---	1	Beryllium Copper	---	
⑦	Lever	---	1	Stainless Steel	---	

APPROVALS		DATE	ELECTRONICS CO.,LTD	
DRAWN	J.X.Zhang	2013/11/6	MICRO SWITCHS	

APPROVALS		TITLE:	PART NO.
CHECKED			K9-1267G-G116

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	ANGLE	UNIT:	SCALE:	DRAWING NO.	SHEET
	A		NEW				30~0.1t 10~0.30 5~0.10	±2°	mm	1:1		1 OF 1