



Circuit Diagram

- NOTE:
1. Rating: AC125V 5A/250V 3A
 2. Operating force: 30±10gf
 3. Mechanical Life: 1,000,000
 4. Electrical Life: 6000-10,000

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
①	Aluminum rivet	—	1	Aluminum Alloy	—	—
⑩	Spindle	—	1	Brass	Plating Nicke	—
⑨	Roller	—	1	Brass	Plating Nicke	—
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Lever	—	1	Stainess Steel	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—

APPROVALS	DATE	TITLE:
DRAWN J.X.Zhang	2014/7/21	MICRO SWITCHS
CHECKED		
APPROVALS		

TOLERANCES ARE	±0.30	ANGLE	PART NO.	SCALE:	PROD.
30~81.4	±0.25	±2°	K9-1910F	1:1	OKHRO
10~20	±0.20				
5~10	±0.20				
~5	±0.20				

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			



ELECTRONICS CO.,LTD

MICRO SWITCHS

K9-1910F

SCALE: 1:1

DRAWING NO. SHEET 1 OF 1